

ECO CAF® 3-OG



ECO CAF 3-OG Compressed Air Foam System is designed to meet the budgetary restraints of both fire departments and industry nationwide. ECO CAF 3-OG uses no outside pressure vessel to operate 100 - 120 PSI from a standard air compressor. ECO CAF 3-OG dispenses approximately 30 gallons of finished foam. Light weight and compact, the ECO CAF 3-OG can use any style of foam concentrate including Class A, B and AR foams. ECO CAF prefers BioEx brand of foam. In a time when everyone is feeling the pinch, ECO CAF® is leading the way with effective, economical solutions for today's fire fighting needs.

PERFORMANCE

- Pressure Vessel Capacity: 3 Gal.
- Finished Foam Capacity: Up to 30 Gal.
- Gallons Throw Distance: Up to 40 Ft.
- Foam Expansion: 20:1 Expansion Ratio

SPECIFICATIONS

- Width: 9 1/2" Height: 28" Diameter: 10"
- Weight Empty: 9.5 lbs.
- Weight Full: 18 lbs.
- Operating Pressure: 100 – 120 PSI.
- Discharge Hose: 3/8" x 20" Hard Rubber Handheld Line
- Discharge Tip: Plastic Straight Tip
- Expellant
- Stainless Steel Oil-Filled Gauge
- Type: Compressed Air
- Foam Types: Can use any style of foam concentrate including Class A, B and AR Foams. Prefer BioEx brand of foam.

